



www.grimco.com

Duratex 10oz Matte Banner

Physical Properties Data Sheet

| Article name: Duratex 10oz Matte Banner | | | |
|---|-------------------------------|--------------------|-------------------|
| Description: 10 oz (200D x 300D / 18 x 12) Matte Banner | | | |
| Sample sheet : | | | |
| Physical Properties | Data | Unit | Test Method |
| Unit Weight | 340±10 | g / M ² | DIN EN ISO 2286-2 |
| Polyester Fabric Yarn (W/F) | 200D x 300D / 18 x 12 | Denier/fd per inch | DIN EN ISO 2060 |
| Tensile Strength Warp/Woof | 610(Warp) | N/ 5cm | DIN 53354 |
| | 173(Woof) | N/5cm | |
| Tearing Strength Warp/Woof | 62(Warp) | N/5cm | DIN 53363 |
| | 29(Woof) | N/5cm | |
| Caliper, mm | 0.255±0.005 | mm | |
| Caliper, mil | 10.0± 0.4 | mil | |
| Gloss @ 60o / Front side | 8-10 | | UNI GLOSS 60Plus |
| Opacity % | 30.0% | | LS117 |
| Color of PVC Banner / Front side (L*, a*, b*) | L = 94.46 | | CM-2500d |
| | a= 1.94 | | |
| | b = -6.48 | | |
| Batch To Batch The Product Color Difference Value $\Delta E \leq 1.0$ | | | |
| Ink Compatible: | ECO Solvent, UV and Latex Ink | | |
| Optional Flame Retardant Treatment | Normal | NFPA 701 | |
| Testing Environmental Condition: Ambient ~ 24°C / 44% Relative Humidity | | | |